Technical Data Sheet



ALL-PURPOSE INK WASH

A VERSATILE, SOLVENT-BLEND INK WASH FOR MOST SCREEN PRINTING INKS

All-Purpose Ink Wash is a blend of solvents for the manual removal of virtually all screen printing inks. All-Purpose Ink Wash can also be used as an activator for dried Walk Away Haze Remover (for instructions, see the Walk Away Haze Remover Technical Data Sheet).

INSTRUCTIONS

Step 1: APPLY ALL-PURPOSE INK WASH

Wear gloves, goggles, and protective clothing. Remove as much ink as possible with a scraper. Soak a work rag with **All-Purpose Ink Wash** and rub it on both sides of the screen until the remaining ink is dissolved and can be wiped from the stencil.

Step 2: RINSE ALL-PURPOSE INK WASH AND DISSOLVED INK FROM THE SCREEN

Rinse the screen thoroughly with water. If any ink remains, apply additional **All-Purpose Ink Wash** to the screen and brush it every minute or two until the ink is dissolved. Remove the ink residue with a work rag and rinse the screen thoroughly with water.

CAUTION

Avoid contact with skin and eyes. Wear gloves, goggles, and protective clothing. Work in a well ventilated area and to not breathe **All-Purpose Ink Wash**'s fumes. Rinse any residue of **All-Purpose Ink Wash** from the screen with water or **Citrus Screen Opener**, as **All-Purpose Ink Wash** has a high flash point and can attack frame adhesives if dwell time is excessive.

PRODUCT DATA

Flash point:	156° F. (69° C.)	
VOC:	7.38 pounds/gallon (923 grams/liter)	
Vapor pressure:	<0.5 mm/Hg at 68° F. (20° C.)	
TLV:	100 ppm	
	2-Methoxymethylethoxypropanol	
HMIS ratings:	Health: 1; Flammability: 1; Reactivity: 0	
Color:	clear	
Shelf life:	1 year at 68° F. (20° C.)	
Disposal:	All-Purpose Ink Wash can generally be washed down drains and is biodegradable in adapted waste-water	
-	treatment facilities, but this should be verified with a review of the Material Safety Data Sheet with local authorities.	

FORMATS

All-Purpose Ink Wash is available in 1 quart (946 cc.), 1 U.S. gallon (3.78 lt.), 5 U.S. gallon (18.92 lt.), and 50 U.S. gallon (189.25 lt.) units. Quarts are packages 12 per carton; U.S. gallon units are packaged 4 per carton; 5 and 50 U.S. gallon units are packaged individually.

806dm

Ulano Corporation, 110 Third Avenue, Brooklyn, NY 11217(USA). Tel: +1 718 237 4700; Fax: +1 718 802 1119; e-mail: <ulano@ulano.com> Ulano International (V.I.), Inc., CH-8952 Schlieren-Zurich (Switzerland). Tel: +41 1 755 44 77; Fax + 41 1 773 16 06; e-mail: <ulanoeurope@ulano.com> www.ulano.com