



Technical Data Sheet

HAZE REMOVER PASTE No. 78

**A STENCIL SCUM AND INK HAZE REMOVER. EFFECTIVE ON MOST INKS & EMULSIONS.
FOR INDUSTRIAL USE ONLY.**

FOLLOW INSTRUCTIONS CAREFULLY TO AVOID WEAKENING THE FABRIC.

CAUTION

Haze Remover Paste No. 78 is for industrial use only.

Use **Haze Remover Paste No. 78** under good ventilation. Avoid prolonged breathing of vapors and contact with the skin. Wear rubber gloves to protect the hands. Use goggles to protect the eyes. Wear protective clothing.

Haze Remover Paste No. 78 is flammable: do not use it near heat or open flames. **Haze Remover Paste No. 78** is corrosive and contains caustic soda, such that it causes severe burns on contact. Avoid contact with skin, the eyes, mucous membranes, and clothing. It is harmful or even fatal if swallowed. Flush spills immediately with water mixed with equal parts of vinegar.

FIRST AID

EYES: Flush the eyes immediately with water and continue for at least 20 minutes.

EXTERNAL CONTACT: Flood the affected area with water for at least 15 minutes; then wash the exposed area with a solution of equal parts of vinegar and water.

INGESTION: Drink large quantities of water or milk followed by citrus juice or diluted vinegar. Do not induce vomiting. Call a physician or emergency medical services immediately.

INSTRUCTIONS

Step 1: PREPARE THE HAZE REMOVER PASTE No. 78

Mix the contents thoroughly.

Step 2: APPLY HAZE REMOVER PASTE No. 78 TO THE SCREEN

Brush **Haze Remover Paste No. 78** briskly on both sides of the screen with a long-bristle nylon brush. Let the screen stand for ten minutes—no longer.

For very stubborn stains, wet the screen with the proper ink solvent on both sides before brushing on **Haze Remover Paste No. 78**.

Step 3: RINSE OFF THE SCREEN WITH AN UNPRESSURIZED FLOW OF WATER

Hold the screen vertically in a washup sink or cleanup shower. Wet both sides of the screen with a gentle spray of water. Open the nozzle of the hose so that water flows down the screen on both sides, washing away the **Haze Remover Paste No. 78**. This technique prevents chemical residues from splashing back onto the worker.

Step 4: REMOVE HAZE AND STAINS WITH A COMMERCIAL POWER SPRAY OR POWER WASH

Once the screen is free of chemical residues, adjust the nozzle or spray unit to its highest level—or use a commercial power spray or power wash at a very high pressure setting to remove haze and stains.

1213dm



Technical Data Sheet

www.ulano.com
